



Southeast Toyota Distributors, LLC

**Southeast Toyota Distributors, LLC
Accessory Installation Instructions**

**2020 Rav4
Dual Smart USB Power Port
(Rear CLA Removal)**

Year & Model:	2020 Rav4
Part Number:	00016-00325
Accessory Code:	CP1000
PIO / DIO:	PIO / DIO
Business Partner:	J56

Conflicts

Note: Factory USB

General Applicability

Fits Models	
1	2020 Models, LE Models

Additional Items Required For Installation

Item#	Description:
1	N/A

Sequence of Application

Item#	Accessory:
1.	N/A
<p><u>SPECIALNOTE: Installation Sequences</u> After TMS & Safety mandated preparatory steps have been taken, the installation sequence is the suggested method for completing the accessory installation. In some instances the suggested sequence is written for one associate to install & in others the sequence is given as part of a team accessory installation. Unless otherwise stated in the document, the associates may perform the installation steps in any order to make the installation as efficient as possible while maintaining consistent quality.</p>	

Recommended Tools

Safety Tools	
Safety Glasses	
Special Tools	
Volt Meter (USB Tester)	
Installation Tools	
	Notes
Trim Panel Removal Tool	
Torque Wrench	48 in. lbs.
Ratchet/ Driver	
Socket	10mm
Padded Work Surface	
Side Cutters	
Needle Nose Pliers	
Protective Blankets	
CLA Removal Tool	
Small Flat Head (Taped)	
Special Chemicals	
N/A	

STOP: Damage to the vehicle may occur. Do not Proceed until process has been complied with.

OPERATOR SAFETY: Use caution to avoid risk of injury.

CAUTION: A process that must be carefully observed in order to reduce the risk of damage to the accessory/vehicle and to ensure a quality installation.

TOOLS & EQUIPMENT: Used in figures calls out the specific tools and equipment recommended for this process.

REVISION MARK: This mark highlights a change in installation with respect to previous issue.

SAFETY TORQUE: This mark indicates that torque is related to safety.

REGULATORY MARK: This mark indicates that the component is related to regulatory compliance.

VIDEO: This image indicates a video to show a installation procedure, PIO Only.

Table of Contents

- I. Preparation.....1-5
 - a.) Table of Contents.....2
 - b.) Kit/Hardware & Wire Harness Bag Contents.....3
 - c.) Parts for Installation.....4
 - d.) Service & Warranty Information.....5

- II. Procedures
 - a.) Battery Removal.....6
 - b.) Vehicle Disassembly –Installation Process.....7-14

- III. Re-install Battery.....15
- IV. Function and Quality Check.....16
- V. Diagnostic /Block Diagrams & Connectors Procedures.....17-18
- VI. Warranty Statement.....19-20

Kit/Hardware Bag Contents:

Item #	Quantity	Description
1.	1	Dual Smart USB Power Port
2.	2	RED #951 Female T-Taps
3.	2	BLUE #952 Female T-Taps
4.	2	Foam Tape Squares 2" x 2"
5.	7	Zip Ties 8"

Care must be taken when installing this accessory to ensure damage does not occur to the vehicle. The installation of this accessory should follow approved guidelines to ensure a quality installation. These guidelines can be found in the “Accessory Installation Practices” document.

This document covers such items as:

- Vehicle Protection (use of covers and blankets, cleaning chemicals, etc.).
- Safety (eye protection, re-checking torque procedure, etc.).
- Vehicle Disassembly/ Reassembly (panel removal, part storage, etc.).
- Electrical Component Disassembly/Reassembly (battery disconnection, connector removal, etc.).

Parts for Installation:

Item #	Quantity	Description
1.	1	Dual Smart USB Power Port
2.	2	RED #951 Female T-Taps
3.	2	BLUE #952 Female T-Taps
4.	2	Foam Tape Squares 2" x 2"
5.	7	Zip Ties 8"



Service & Warranty Information:

Image Key	Parts Information		Warranty Information	
	Part Number	Description	Warranty Time	Labor Op. Code
A	00016-00325	Dual Smart USB Power Port	0.3	ACP001

Labor times include consideration for diagnosis and Administration time.
 If you are a dealer located outside of the Southeast Region, please contact the SET Accessory Warranty Department at (888) 851-2722 or email Accessory.Warranty@SEToyota.com for claim payment instructions.

Parts:

A – Dual Smart USB Power Port Kit







Figure 1-1

1. Prepare for the Installation:
 - a. The engine components and coolant may be hot.
 - b. Check the kit for contents and any damage.
 - c. Protect the fender.

Battery Removal-Gas Models

Note: The battery is in the engine compartment. See Figure 1-1

 Do not disconnect the terminal at the 12mm nut.




 Use 10mm socket.



Figure 1-2

2. Remove the NEGATIVE (-) battery terminal by loosening the 10mm terminal nut before starting any disassembly. See Figure 1-2.

 DO NOT touch the positive terminal.

 Wait at least 90 seconds after disconnecting the cable from the negative (-) battery terminal to disable the SRS system.




Figure 3-1




Figure 3-2




Figure 3-3




Figure 3-4

3. Battery Removal-Hybrid Models


Note: The battery is in the rear cargo area.


a. Remove the deck board assembly. See Figure 3-1.


b. Detach the 2 clips and 2 guides and remove the luggage trim service hole cover. See Figure 3-2.

c. Detach the 12 claws and remove the battery hole cover. See Figure 3-3.

d. Loosen the nut, and disconnect the cable from the negative (-) auxiliary battery terminal. See Figure 3-4.

 Use 10mm socket.

 DO NOT touch the positive terminal.

 Wait at least 90 seconds after disconnecting the cable from the negative (-) battery terminal to disable the SRS system.




Figure 2




Figure 3

Vehicle Disassembly-Installation Process

4. REMOVE REAR CONSOLE END PANEL SUB-ASSEMBLY

(a) Pull in the direction indicated by the arrow to detach the clip and claw.
Figure 2.

5. Disconnect each connector and remove the rear console end panel sub-assembly.

6. REMOVE NO. 3 POWER OUTLET SOCKET ASSEMBLY (W/o USB Charger)

Using a screwdriver with its tip wrapped with protective tape, detach the claw and remove the No. 3 power outlet socket assembly as shown in figure 3.

HINT: Tape the screwdriver tip before use.



Figure 4

Optional Step: Use a SST cigarette lighter removal tool

7. Detach the claw and guide to remove the No. 3 power outlet socket cover using the CLA Removal Tool. Figure 4



Note: One side of the "T" portion of the CLA tool must be placed in the tab window & then the other should be angled into the opposite window. The lighter socket can then be pulled straight out of its mounting hole. **CAUTION:** Remove the cigarette lighter fuse before using this tool. See illustration below.





Figure 5



IIIUSTRATION

8. REMOVE NO. 3 POWER OUTLET SOCKET COVER (W/o USB Charger) Figure 5.



Figure 6

9. Unscrew nut and remove lock washer then feed the power and ground wires through the 1" hole from the outside of the center lower instrument panel finish panel. See Figure 6.




Figure 7

10. Feed the power and ground wires through the lock washer and nut. The lock washer goes on first. See Figure 7.




Figure 8



- 11 . Hand-tighten the nut until snug. See Figure 8.

T-TAP INSTALLATION





When installing the female T-Tap connectors, be sure the wire is located inside the wire channel of the female T-Tap connector before closing the connector over the wire with pliers.



CONNECTOR N10 #2 Power Outlet Socket Assembly)

Location: Lower center instrument panel finish panel

USB POWER PORT	VEHICLE	PIN	T-TAP
Red - Power	Red	1	Blue
Black - Ground	White/Black	2	Blue



Examples

Note : Install the T-Taps in a staggered position on the wires. T-Taps should not be side by side nor same distance from the connector. There should be approximately at least one inch of wire remaining between the connector and the closest t-tap to the connector. See Examples 1 & 2.



Figure 8




Figure 9

T-TAP REAR OUTLET'S POWER & GROUND WIRES.

12. Locate the white connector N10 for (1 Pin) rear power outlet socket at the center rear instrument finish panel.
13. Pull back the protective tape, if necessary to expose at least 2" of the power & ground wires behind the connector on the vehicle side.
14. Separate the RED power wire from the WHITE/BLACK ground wire.



Hold the exposed wires when pulling back the protective tape. Do not pull the wires from the connector.

15. T-Tap the BLUE power wire (Pin 1) & the WHITE/BLACK ground wire (Pin 2) from connector N10 using the supplied BLUE T-Tap female connectors. See figure 8.

16. Before connecting, make sure the USB Power Dock's male spade connectors are not bent to one side to ensure they insert securely into their corresponding female T-Tap connectors.



Do not reverse the power & ground connections or the USB Power Port will be damaged.

17. Connect the male spade connector of the USB Power Port's RED power wire to the N10 connector's RED power wire T-tap (Pin 1).

Connect the male spade connector of the USB Power Port's BLACK ground wire to the N10 connector's WHITE/BLACK ground wire T-tap (Pin 2). See Figure 9.

SECURE REAR POWER OUTLET'S POWER & GROUND WIRES.

18. Bundle the USB Power Port's power & ground wires to remove most of the slack.

19. Secure the power & ground wire bundle with the supplied 8" zip ties to the factory wire harness as shown. See Figure 10.

Snip the excess zip tie lengths.




Figure 10

20.

INSTALL REAR CONSOLE END PANEL SUB-ASSEMBLY

Connect each connector. If applicable

(b) Attach the clip and claw to install the rear console end panel sub-assembly in the direction indicated by the arrow shown in the illustration. See figure 11a.




Figure 11a.



Figure 11b.



Figure 12








Figure 13

Re-install Battery

-  21. Tighten the negative battery cable. See Figure 12 and Figure 13.

 Torque: 48 in•lbs [5.4 N•m]

 Caution: DO NOT touch the positive terminal.

 When disconnecting the cable, some systems need to be initialized after the cable is reconnected.

Hybrid Models

- a. Attach the 12 claws and install the battery hole cover.
- b. Attach the 2 clips and 2 guides and install the luggage trim service hole cover.
- c. Install the deck board assembly.

22. Print Warranty Statement and place in the glove box, DIO only.

FUNCTION AND QUALITY CHECK

These points MUST be checked to ensure a quality installation.

ACCESSORY FUNCTION CHECK

✓ Alignment

USB power ports are aligned Vertically.

✓ Turn ignition (ACC power) to On.

LED power status light is on.
Each USB port supplies power to both sides of a USB. Factory power outlet supplies power.

✓ Warranty Statement

Place Warranty Statement in the glove box, DIO Only.

Diagnostic /Block Diagrams & Connectors Procedures

EWD - Block Diagram
Dual USB Power Port
Part Number: 00016-00325
Parasitic Draw = 2.0mA Max Power Draw = 24W

Connects to
ACC circuit
@ N10 pin 2

C2

B

Connects to
ACC circuit
@ N10 pin 1

C1

R

USB Power Port
Part Number: 00016-00325

5V/2.4A

5V/2.4A

Diagnostic /Block Diagrams & Connectors Procedures



Connector C1

Pin	Wire Color	Test Reference	Proper Operation
1	Red	Pin 1 to Power	Approximately 0 VDC when ignition switch is OFF +12 VDC when ignition switch is ON



Connector C2

Pin	Wire Color	Test Reference	Proper Operation
2	Black	Pin 2 to Ground	Approximately 0 VDC

LIMITED WARRANTY – SOUTHEAST TOYOTA

SOUTHEAST TOYOTA DISTRIBUTORS, LLC ("we," "our" and "us") provides the following limited warranty on our accessories, excluding tires, ("Accessories" or "Accessory") installed on a Toyota. This limited warranty is not provided by and does not bind or provide benefit to the vehicle dealer, the manufacturer, or Toyota Motor Sales, U.S.A., Inc. This limited warranty does not apply to tires; please consult the tire manufacturer and/or its materials accompanying the vehicle for any warranty terms concerning tires. This limited warranty also does not apply to ToyoGuard Exterior Paint Sealant and ToyoGuard Interior Protector; please consult the ToyoGuard Limited Warranty Certificate for the warranty terms concerning those products.

SCOPE OF LIMITED WARRANTY:

A. Protection:

- i. **Accessories Installed by Southeast Toyota Distributors, LLC on a new Toyota vehicle.** We warrant that, for a period of 36 months or 36,000 miles, whichever occurs first, we will repair or replace (includes labor), free of charge, any defect in such an Accessory due to faulty material or workmanship, or, at our option, provide a full refund of the purchase price of the Accessory. The warranty period begins on the vehicle's In-Service Date, which is the first date the new vehicle is either delivered to an ultimate purchaser, leased, or used as a company car or demonstrator. Accessories installed by Southeast Toyota Distributors, LLC are identified on the vehicle's window sticker (Monroney Label).
- ii. **Accessories Installed by a Toyota Dealer on a Toyota vehicle.** We warrant that, for 12 months, regardless of mileage, from the date such an Accessory was installed on the vehicle or the remainder of the Toyota new vehicle warranty, whichever is longer, we will repair or replace (includes labor), free of charge, any defect in the Accessory due to faulty material or workmanship, or, at our option, provide a full refund of the purchase price of the Accessory. For a new vehicle, the warranty period begins on the vehicle's In-Service Date, which is the first date the new vehicle is either delivered to an ultimate purchaser, leased, or used as a company car or demonstrator.
- iii. **Accessories purchased from a Toyota Dealer but not installed by the Toyota Dealer.** We warrant that, for a period of 12 months, regardless of mileage, from the date the accessory was purchased, we will repair or replace (does not include labor), free of charge, any defect in the Accessory due to faulty material or workmanship, or, at our option, provide a full refund of the purchase price of the Accessory.

B. Limitation of Warranty. This limited warranty does not apply to, and we will not repair, replace, or reimburse you for: (1) wheel balancing and wheel alignments, except for one wheel balancing or alignment during the first 12 months or 12,000 miles, whichever occurs first, from the vehicle's In-Service Date, as defined above, (2) abrasions or dents, whatever their cause, and any failure or damage resulting directly or indirectly from accidents, collisions, impacts from foreign objects, fire, theft, larceny, explosion, malicious mischief, vandalism, civil commotion, riots, war, or any other similar causes, (3) any failure or damage resulting directly or indirectly from lightning, windstorms, hail, water, floods, subfreezing temperatures, airborne chemicals, tree sap, dust, salt, and any other environmental conditions or similar causes, (4) any failure or damage caused by: (a) a failure of any part, other than the Accessory, (b) any misuse, abuse, improper towing, negligence or lack of maintenance of the vehicle or Accessory, (c) the alteration, modification or repair of the Accessory by anyone other than persons expressly authorized by us to perform such alteration, modification or repair, or (d) the use of the vehicle for commercial purposes, competitive driving or racing, (5) any failure or damage, if the Accessory has not been installed according to instructions, (6) any failure or damage occurring outside of Canada, the United States of America, its territories or possessions, (7) except to the extent required by the state whose laws govern this limited warranty, any consequential, secondary, or unreasonable costs that may be suffered as a result of the need to repair or replace the Accessory, including without limitation any loss of use of the vehicle, road service, towing, storage charges, inconvenience, loss of wages and/or income, additional expense incurred, loss of transportation, rental car expense, or any derivative damage to persons or things other than the Accessory, including other parts of the vehicle, or (8) liability for damage to property or for injury to or death of any person, arising out of the operation, maintenance or use of your vehicle whether or not related to the covered Accessory.

C. Exclusive Remedy. If there is a valid claim under this limited warranty for a defect due to faulty material or workmanship in the Accessory, we will, at our option, either: (i) repair, (ii) replace or (iii) provide a full refund of the purchase price of the Accessory. We have no other obligations under this limited warranty. Refunds will be made to the vehicle owner. If the vehicle is leased, the refund will be made to the leasing company.

HOW TO MAKE A CLAIM: In the event of a warranty claim, please contact the nearest Toyota dealer to arrange for repairs. The dealership must receive our prior authorization before making repairs covered by this limited warranty. The dealer will contact Southeast Toyota Distributors, LLC at 1-888-851-2722, select option #5 (Warranty Department), then option #4 (Repairs), for instructions on processing a warranty claim, if they are not already familiar with the process. If you have any questions or concerns regarding repairs covered by this limited warranty, please contact our Customer Assistance Hotline at 1-800-301-6859.

OUR DISPUTE RESOLUTION PROGRAM: Your satisfaction is our highest priority. In keeping with that focus, in the event that an issue arises related to this Limited Warranty, we invite you to call our Customer Assistance Hotline at 1-800-301-6859 to discuss it. In most cases, we expect that a satisfactory resolution of your issue can be reached through engagement with that Department. If our Customer Loyalty Department is unable to resolve your issue to your satisfaction, we offer a dispute resolution program administered by the National Center for Dispute Settlement (NCDS) ("the Program"). The purpose of the Program is to resolve disputes in an informal setting before an impartial arbitrator. The Program is free of charge to you (although you must bear the cost of any expert witness or attorney you elect to employ). You are required to complete the Program before exercising rights or seeking remedies under the federal Magnuson-Moss Warranty Act, 15 U.S.C. § 2301 et seq. ("the Act"). If you choose to seek remedies that are not created by the Act, you are not required to use the Program before pursuing such remedies – although the Program is still available to you to resolve the dispute. When utilizing the Program, you will need to provide (a) the vehicle identification number of your vehicle, (b) the identity of your selling and servicing dealerships, (c) the mileage on your vehicle at relevant times, (d) the date and nature of any relevant repairs, (e) legible copies of repair orders and other relevant documents, (f) a summary of the unresolved issue and the requested action, and (g) your contact information. In most cases, the dispute resolution process under the Program will be completed within forty (40) days of your submission of your request and will consist of steps such as an initial eligibility determination, an opportunity for you and us to submit information in writing relating to your claim, an oral hearing, and a decision from the arbitrator. A decision will be binding on you only if you choose to accept it. You may submit a request to NCDS by telephone at their toll free number: (877)-276-8848 or in writing at P.O. Box 463196, Mt. Clemens, MI 48046. You may obtain additional information regarding the Program at www.ncdsusa.org. In the event that the NCDS does not exist or no longer handles disputes for us at the time that you seek to submit a request, you may contact our Customer Assistance Hotline at 1-800-301-6859 to obtain current information about our dispute resolution programs.

GENERAL LIMITATION OF WARRANTY: THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS WARRANTIES OR LIABILITIES. IN NO EVENT SHALL WE BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES FOR BREACH OF THIS OR ANY OTHER WARRANTY. SOME STATES DO NOT ALLOW THE EXCLUSIONS OR LIMITATIONS OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE INFORMATION OR EXCLUSION MAY NOT APPLY. NO EXPRESS WARRANTY OF FITNESS OR MERCHANTABILITY IS GRANTED BY THIS LIMITED WARRANTY. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THOSE DESCRIBED IN THIS DOCUMENT. ANY IMPLIED WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, WHICH MAY BE APPLICABLE BY OPERATION OF LAW SHALL BE LIMITED TO THE PERIOD OF THIS WRITTEN LIMITED WARRANTY. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATIONS MAY NOT APPLY. THIS LIMITED WARRANTY PROVIDES SPECIFIC LEGAL RIGHTS, AND THERE MAY BE OTHER RIGHTS WHICH VARY FROM STATE TO STATE. ANY ACTION FOR BREACH OF ANY WARRANTY HEREUNDER, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, MUST BE BROUGHT WITHIN A PERIOD NOT EXCEEDING 12 MONTHS AFTER EXPIRATION OF THIS LIMITED WARRANTY. THE REMEDIES SPECIFIED HEREIN AND THOSE SPECIFIED BY APPLICABLE LAW ARE THE ONLY REMEDIES AVAILABLE. WE ASSUME NO OTHER OBLIGATION OR RESPONSIBILITY WITH REGARD TO THE ACCESSORY. WE NEITHER ASSUME, NOR AUTHORIZE ANYONE TO ASSUME FOR US, ANY ADDITIONAL LIABILITY IN CONNECTION HEREWITH.

GENERAL: This limited warranty describes the complete and exclusive rights that result from the purchase of Accessories. No oral representations or statements may be relied upon. This limited warranty may not be amended or modified, and additional rights may not be granted, unless in a written statement signed by one of our officers. This limited warranty shall be governed by the laws of the state where the vehicle is purchased, excluding laws concerning conflicts of law. We may delegate the performance of our duties and obligations and assign our rights and benefits hereunder. For inquiries regarding this limited warranty, we can be contacted directly at **Customer Assistance Hotline at 1-800-301-6859**, or by mail to: **Southeast Toyota Distributors, LLC, Attention: Customer Loyalty Department, 100 Jim Moran Boulevard, Deerfield Beach, Florida 33442.**