



Southeast Toyota Distributors, LLC Accessory Installation Instructions

2018 Tundra Power Tailgate Lock

Year & Model:	2018 Tundra
Part Number:	00016-34092
Accessory Code:	TL1000
PIO / DIO:	PIO / DIO
Business Partner:	J64

Conflicts

Note: Vehicles without Keyless Entry

General Applicability

Fits Models:

Note: 2018 Tundra Models with Keyless Entry

Additional Items Required For Installation

Item#	Description:
1.	N/A

Sequence of Application

Item#	Accessory:
1.	N/A
<p><u>SPECIAL NOTE: Installation Sequences</u> After TMS & Safety mandated preparatory steps have been taken, the installation sequence is the suggested method for completing the accessory installation. In some instances the suggested sequence is written for one associate to install & in others the sequence is given as part of a team accessory installation. Unless otherwise stated in the document, the associates may perform the installation steps in any order to make the installation as efficient as possible while maintaining consistent quality.</p>	

Recommended Tool

Safety Items	
N/A	
Installation Tools	
8 & 10mm Wrench/Socket	T30 Torx Bit Driver
Small Flat Screwdriver	
Pliers	
Torque Wrench	
Drill / 11/32 Drill Bit	
Special Chemicals	
VDC Approved Cleaner	

Legend

	STOP: Damage to the vehicle may occur. Do not proceed until process has been complied with.
	OPERATOR SAFETY: Use caution to avoid risk of injury.
	CAUTION: A process that must be carefully observed in order to reduce the risk of damage to the accessory/vehicle and to ensure a quality installation.
	TOOLS & EQUIPMENT: Used in Figures calls out the specific tools and equipment recommended for this process.
	REVISION MARK: This mark highlights a change in installation with respect to previous issue.
	SAFETY TORQUE: This mark indicates that torque is related to safety.

Table of Contents

I.	Preparation.....	1-5
a.)	Table of Contents.....	2
b.)	Kit/Hardware Bag Contents.....	3
c.)	Parts for Installation.....	4
d.)	Service & Warranty Information.....	5
II.	Procedures	
a.)	Remove Negative Battery Cable.....	6
b.)	Installation Process.....	7-12
c.)	Quick Spice Connectors Procedures.....	12
III.	Wiring Diagram & Connectors.....	13
IV.	Vehicle Function Checks.....	14
V.	Warranty Statement.....	15-16

Kit/Hardware Bag Contents:

Item #	Quantity	Description
1.	1	Power Lock Assembly
2.	1	Long Wire Harness
3.	1	Short Wire Harness
4.	2	Wire Taps
5.	25	Cable Ties

Parts for Installation:

Care must be taken when installing this accessory to ensure damage does not occur to the vehicle. The installation of this accessory should follow approved guidelines to ensure a quality installation. These guidelines can be found in the “Accessory Installation Practices” document.

This document covers such items as:

- Vehicle Protection (use of covers and blankets, cleaning chemicals, etc.).
- Safety (eye protection, re-checking torque procedure, etc.).
- Vehicle Disassembly/ Reassembly (panel removal, part storage, etc.).
- Electrical Component Disassembly/Reassembly (battery disconnection, connector removal, etc.).

Item #	Quantity	Description	Part Number
1.	1	Power Lock Assembly	00016-34092



Image Key	Parts information		Warranty Information	
	Part Number	Description	Warranty Time	Labor Op. Code
A	00016-34092	Tailgate Power Lock	0.5	ALO001

Labor times include consideration for diagnosis and Administration time

If you are a dealer located outside of the Southeast Region, please contact the SET Accessory Warranty Department at (888) 851-2722 or email Accessory.Warranty@SEToyota.com for claim payment instructions.

Image:



Remove Negative Battery Cable:**DO NOT TOUCH THE POSITIVE TERMINAL**

Wait at least 90 seconds after disconnecting the cable from the negative (-) battery terminal to disable the SRS system.




Fig. 1



Fig. 2

1. Remove the T-30 Torx screws that hold the access panel on the inside of the tailgate and remove the access panel.
2. Unclip and remove both latch rods. Do this by rotating the clip off the rod and lifting the rod out of the clip (You may need to use a small screw driver to rotate clip). Lay them to the side.



Fig. 3

3. Remove the passenger side 8mm or 10mm mounting bolt.


Installation Process:

Fig. 4

4. Mount the power lock inside the tailgate to the passenger side of the handle. One hole in the bracket will align with the mounting bolt removed in the last step. The other hole will straddle a plastic post on the handle (see arrow). Insert the handle mounting bolt into the hole and tighten. The factory locking arm will lie between the two tabs on the power lock slide bar. Fig. 4

Note: The actuator obscures the mounting bolt, you will have to start the mounting bolt by hand and tighten it using a wrench & reattach latch rods.




Fig. 5

5. Remove 2 OE harness clips for tailgate and notch both as in Fig. 5 . Wire tie Tailgate Lock Harness to OE Tailgate Harness only. This will make it easy to unplug for tailgate removal.



Fig. 6

6. Mark bottom of 2 OE harness clips for tailgate and drill 11/32 holes. Fig. 6 & 7
Wire tie Tailgate Lock Harness to OE Tailgate harness only. This will make it easy to unplug tailgate removal.



7. Bed side of harness with bottom marked to drill hole. Fig. 6



Fig. 8

8. Bed side of harness with clip installed and harness routed. Fig. 7




Fig. 9

9. Tailgate side of harness with bottom marked to drill hole. Fig. 8

10. Tailgate side of harness with clip installed and harness routed. Fig. 9



Fig. 10



Fig. 11

11. Connect the bullet connectors to the actuator on the power lock maintaining green to green and blue to blue. Roll up and secure extra wire with a cable tie. Fig. 10 & 11



Fig. 12

12. Connect the delphi end of the long wire harness to the delphi end of the short harness. Secure the long wire harness under the truck bed maintaining easy access to the delphi plug for tailgate removal. Also make sure the tailgate can be open and closed without pinching any part of the connector or the wire. Fig. 12

Note: Do not secure any part of the short harness to the actual truck or tailgate won't be able to be removed.




Fig. 13

13. Run the long wiring cable down under the bed of the truck and along the passenger side frame rail, securing it about every 16 inches with the cable ties. Run the wire up to the passenger side lower corner of the fire wall. Fig. 13

Note: Make sure to secure the wire so it does not touch the exhaust or get pinched.



Fig. 14

14. Lock harness at tailgate harness. Fig. 14



Fig. 15

15. Harness on passenger side of spare tire. Fig. 15



Fig. 16

16. Harness ran along frame rail above exhaust. Fig 16



Fig. 17

17. Coutinuing along frame. Fig. 17



Fig. 18

18. Ending at grommet under cab. Fig. 18




Fig. 19

19. Locate the rubber grommet for the main factory wiring harness in the lower passenger side corner of the fire wall. Cut a small slit in the upper part of the grommet. Snake all available long wiring cable through the slit into the cab of the truck. Seal with VDC approved sealant. Fig. 19



Fig. 20

20. Remove the passenger's side kick panel. Start by removing the nut that holds the kick panel on. Gently pull the panel toward you, be careful not to break any of the plastic. Fig. 20





Fig. 21

21. Locate the terminal marked MJ1. This is the bottom blue connector. Splice the blue of the long wire harness to the White wire pin 9, & the Green wire of the power lock to the Red wire pin 18 using the Quick Splice Connectors. Fig. 21






Fig. 22




Fig. 23

Quick Spice Connectors:

22.

- a.) Snap the connector channel onto unstripped factory wire.
- b.) Insert un-stripped wire from the long wire harness into the connector inside channel until it hits the stop.
- c.) Use pliers to cinch down the metal connector tab. Do this by holding the pliers perpendicular to the wires and squeeze the metal tab down into the plastic connector until it is flush with the top of the plastic insulator.
- d.) Close the plastic hinged top cover until latched. Bundle harness as shown in Fig. 23

Note: Re-install negative battery terminal and torque to 48" lbs.



23. The power lock should lock and unlock the tailgate whenever the passenger door is locked or unlocked with the remote or door switch. When unlocking with the remote press the unlock button "Twice".

Note: The tailgate still can be locked and unlocked with the factory key.

Troubleshooting Note:

If the power lock functions opposite of the doors locks, switch the wires at the bullet connectors. Connect the Blue to Green and Green to Blue.





Fig. 24

24. If the power lock functions properly reinstall all removed panels.

25. (DIO, Only) Print Warranty Statement and place in the glove box.

Wiring Diagram & Connectors:



Vehicle Function Checks:

Checklist - these point MUST be checked to ensure a quality installation.

Check : After Installation:

Look For:



Lock properly installed

Locking and unlocking of tailgate.



Remote

Properly working.



Panels

Panels properly reinstalled.



Warranty Statement

Warranty placed in glove box, DIO Only.

LIMITED WARRANTY – SOUTHEAST TOYOTA

SOUTHEAST TOYOTA DISTRIBUTORS, LLC ("we," "our" and "us") provides the following limited warranty on our accessories, excluding tires, ("Accessories" or "Accessory") installed on a Toyota. This limited warranty is not provided by and does not bind or provide benefit to the vehicle dealer, the manufacturer, or Toyota Motor Sales, U.S.A., Inc. This limited warranty does not apply to tires; please consult the tire manufacturer and/or its materials accompanying the vehicle for any warranty terms concerning tires. This limited warranty also does not apply to ToyoGuard Exterior Paint Sealant and ToyoGuard Interior Protector; please consult the ToyoGuard Limited Warranty Certificate for the warranty terms concerning those products.

SCOPE OF LIMITED WARRANTY:

A. Protection:

- i. **Accessories Installed by Southeast Toyota Distributors, LLC on a new Toyota vehicle.** We warrant that, for a period of 36 months or 36,000 miles, whichever occurs first, we will repair or replace (includes labor), free of charge, any defect in such an Accessory due to faulty material or workmanship, or, at our option, provide a full refund of the purchase price of the Accessory. The warranty period begins on the vehicle's In-Service Date, which is the first date the new vehicle is either delivered to an ultimate purchaser, leased, or used as a company car or demonstrator. Accessories installed by Southeast Toyota Distributors, LLC are identified on the vehicle's window sticker (Monroney Label).
- ii. **Accessories Installed by a Toyota Dealer on a Toyota vehicle.** We warrant that, for 12 months, regardless of mileage, from the date such an Accessory was installed on the vehicle or the remainder of the Toyota new vehicle warranty, whichever is longer, we will repair or replace (includes labor), free of charge, any defect in the Accessory due to faulty material or workmanship, or, at our option, provide a full refund of the purchase price of the Accessory. For a new vehicle, the warranty period begins on the vehicle's In-Service Date, which is the first date the new vehicle is either delivered to an ultimate purchaser, leased, or used as a company car or demonstrator.
- iii. **Accessories purchased from a Toyota Dealer but not installed by the Toyota Dealer.** We warrant that, for a period of 12 months, regardless of mileage, from the date the accessory was purchased, we will repair or replace (does not include labor), free of charge, any defect in the Accessory due to faulty material or workmanship, or, at our option, provide a full refund of the purchase price of the Accessory.

B. Limitation of Warranty. This limited warranty does not apply to, and we will not repair, replace, or reimburse you for: (1) wheel balancing and wheel alignments, except for one wheel balancing or alignment during the first 12 months or 12,000 miles, whichever occurs first, from the vehicle's In-Service Date, as defined above, (2) abrasions or dents, whatever their cause, and any failure or damage resulting directly or indirectly from accidents, collisions, impacts from foreign objects, fire, theft, larceny, explosion, malicious mischief, vandalism, civil commotion, riots, war, or any other similar causes, (3) any failure or damage resulting directly or indirectly from lightning, windstorms, hail, water, floods, subfreezing temperatures, airborne chemicals, tree sap, dust, salt, and any other environmental conditions or similar causes, (4) any failure or damage caused by: (a) a failure of any part, other than the Accessory, (b) any misuse, abuse, improper towing, negligence or lack of maintenance of the vehicle or Accessory, (c) the alteration, modification or repair of the Accessory by anyone other than persons expressly authorized by us to perform such alteration, modification or repair, or (d) the use of the vehicle for commercial purposes, competitive driving or racing, (5) any failure or damage, if the Accessory has not been installed according to instructions, (6) any failure or damage occurring outside of Canada, the United States of America, its territories or possessions, (7) except to the extent required by the state whose laws govern this limited warranty, any consequential, secondary, or unreasonable costs that may be suffered as a result of the need to repair or replace the Accessory, including without limitation any loss of use of the vehicle, road service, towing, storage charges, inconvenience, loss of wages and/or income, additional expense incurred, loss of transportation, rental car expense, or any derivative damage to persons or things other than the Accessory, including other parts of the vehicle, or (8) liability for damage to property or for injury to or death of any person, arising out of the operation, maintenance or use of your vehicle whether or not related to the covered Accessory.

C. Exclusive Remedy. If there is a valid claim under this limited warranty for a defect due to faulty material or workmanship in the Accessory, we will, at our option, either: (i) repair, (ii) replace or (iii) provide a full refund of the purchase price of the Accessory. We have no other obligations under this limited warranty. Refunds will be made to the vehicle owner. If the vehicle is leased, the refund will be made to the leasing company.

HOW TO MAKE A CLAIM: In the event of a warranty claim, please contact the nearest Toyota dealer to arrange for repairs. The dealership must receive our prior authorization before making repairs covered by this limited warranty. The dealer will contact Southeast Toyota Distributors, LLC at 1-888-851-2722, select option #5 (Warranty Department), then option #4 (Repairs), for instructions on processing a warranty claim, if they are not already familiar with the process. If you have any questions or concerns regarding repairs covered by this limited warranty, please contact our **Customer Assistance Hotline at 1-800-301-6859**.

OUR DISPUTE RESOLUTION PROGRAM: Your satisfaction is our highest priority. In keeping with that focus, in the event that an issue arises related to this Limited Warranty, we invite you to call our Customer Assistance Hotline at 1-800-301-6859 to discuss it. In most cases, we expect that a satisfactory resolution of your issue can be reached through engagement with that Department. If our Customer Loyalty Department is unable to resolve your issue to your satisfaction, we offer a dispute resolution program administered by the National Center for Dispute Settlement (NCDS) ("the Program"). The purpose of the Program is to resolve disputes in an informal setting before an impartial arbitrator. The Program is free of charge to you (although you must bear the cost of any expert witness or attorney you elect to employ). You are required to complete the Program before exercising rights or seeking remedies under the federal Magnuson-Moss Warranty Act, 15 U.S.C. § 2301 et seq. ("the Act"). If you choose to seek remedies that are not created by the Act, you are not required to use the Program before pursuing such remedies – although the Program is still available to you to resolve the dispute. When utilizing the Program, you will need to provide (a) the vehicle identification number of your vehicle, (b) the identity of your selling and servicing dealerships, (c) the mileage on your vehicle at relevant times, (d) the date and nature of any relevant repairs, (e) legible copies of repair orders and other relevant documents, (f) a summary of the unresolved issue and the requested action, and (g) your contact information. In most cases, the dispute resolution process under the Program will be completed within forty (40) days of your submission of your request and will consist of steps such as an initial eligibility determination, an opportunity for you and us to submit information in writing relating to your claim, an oral hearing, and a decision from the arbitrator. A decision will be binding on you only if you choose to accept it. You may submit a request to NCDS by telephone at their toll free number: (877)-276-8848 or in writing at P.O. Box 463196, Mt. Clemens, MI 48046. You may obtain additional information regarding the Program at www.ncdsusa.org. In the event that the NCDS does not exist or no longer handles disputes for us at the time that you seek to submit a request, you may contact our **Customer Assistance Hotline at 1-800-301-6859** to obtain current information about our dispute resolution programs.

GENERAL LIMITATION OF WARRANTY: THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS WARRANTIES OR LIABILITIES. IN NO EVENT SHALL WE BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES FOR BREACH OF THIS OR ANY OTHER WARRANTY. SOME STATES DO NOT ALLOW THE EXCLUSIONS OR LIMITATIONS OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE INFORMATION OR EXCLUSION MAY NOT APPLY. NO EXPRESS WARRANTY OF FITNESS OR MERCHANTABILITY IS GRANTED BY THIS LIMITED WARRANTY. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THOSE DESCRIBED IN THIS DOCUMENT. ANY IMPLIED WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, WHICH MAY BE APPLICABLE BY OPERATION OF LAW SHALL BE LIMITED TO THE PERIOD OF THIS WRITTEN LIMITED WARRANTY. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATIONS MAY NOT APPLY. THIS LIMITED WARRANTY PROVIDES SPECIFIC LEGAL RIGHTS, AND THERE MAY BE OTHER RIGHTS WHICH VARY FROM STATE TO STATE. ANY ACTION FOR BREACH OF ANY WARRANTY HEREUNDER, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, MUST BE BROUGHT WITHIN A PERIOD NOT EXCEEDING 12 MONTHS AFTER EXPIRATION OF THIS LIMITED WARRANTY. THE REMEDIES SPECIFIED HEREIN AND THOSE SPECIFIED BY APPLICABLE LAW ARE THE ONLY REMEDIES AVAILABLE. WE ASSUME NO OTHER OBLIGATION OR RESPONSIBILITY WITH REGARD TO THE ACCESSORY. WE NEITHER ASSUME, NOR AUTHORIZE ANYONE TO ASSUME FOR US, ANY ADDITIONAL LIABILITY IN CONNECTION HERewith.

GENERAL: This limited warranty describes the complete and exclusive rights that result from the purchase of Accessories. No oral representations or statements may be relied upon. This limited warranty may not be amended or modified, and additional rights may not be granted, unless in a written statement signed by one of our officers. This limited warranty shall be governed by the laws of the state where the vehicle is purchased, excluding laws concerning conflicts of law. We may delegate the performance of our duties and obligations and assign our rights and benefits hereunder. For inquiries regarding this limited warranty, we can be contacted directly at **Customer Assistance Hotline at 1-800-301-6859**, or by mail to: **Southeast Toyota Distributors, LLC, Attention: Customer Loyalty Department, 100 Jim Moran Boulevard, Deerfield Beach, Florida 33442.**