



Southeast Toyota Distributors, LLC Accessory Installation Instructions

2019 Tacoma Console Safe

Year & Model:	2019 Tacoma
Part Number:	00016-35974
Accessory Code:	SC1010
PIO / DIO:	PIO / DIO
Business Partner:	J65

Conflicts

None

General Applicability

Fits Models:	
1.	All 2019 Models
2.	
3.	

Additional Items Required For Installation

Item #	Description:
1	Protective Blankets
2	

Sequence of Application

Item #	Accessory:
1	Dual USB Changer
2	Console Safe

SPECIAL NOTE: Installation Sequences

After TMS & Safety mandated preparatory steps have been taken, the installation sequence is the suggested method for completing the accessory installation. In some instances the suggested sequence is written for one associate to install & in others the sequence is given as part of a team accessory installation. Unless otherwise stated in the document, the associates may perform the installation steps in any order to make the installation as efficient as possible while maintaining consistent quality.

Recommended Tools

Safety Items	
N/A	
Special Tools	
Torque Wrench 0-100 in lbs.	
Installation Tools	
Nylon pry tool - Optional	
10mm socket	
Ratchet or Air Ratchet	
12" extension	
#1 Phillips Screwdriver	
Special Chemicals	
VPC Approved Cleaner	

Legend

	STOP: Damage to the vehicle may occur. Do not proceed until process has been complied with.
	OPERATOR SAFETY: Use caution to avoid risk of injury.
	CAUTION: A process that must be carefully observed in order to reduce the risk of damage to the accessory/vehicle and to ensure a quality installation.
	TOOLS & EQUIPMENT: Used in Figures calls out the specific tools and equipment recommended for this process.
	REVISION MARK: This mark highlights a change in installation with respect to previous issue.
	SAFETY TORQUE: This mark indicates that torque is related to safety.

Table of Contents

I.	Preparation	1
1.	Table of Contents	2
2.	Kit /Hardware Bag of Contents.....	3
3.	Parts for Installation	4
4.	Service & Warranty Information	5
II.	Procedures	
1.	Vehicle Disassembly Process.....	6-7
2.	Vehicle Assembly Process	8-11
III.	Setting Your Own Combination	12
IV.	Vehicle Function & Quality Check.....	13
V.	BlankPage.....	14
VI.	Limited Warranty Statement.....	15-16

Kit/Hardware Bag Contents:

Item #	Quantity	Description
1.	1	Console Safe
2.	1	Hardware Kit
3.	1	Owners Card
4.	1	Lock Key
5.	2	M6 -1.0 x 35mm Bolts
6.	1	Rubber Floor Pad Pre-Cut with Holes
7.	1	Rubber Floor Pad Pre-Cut
8.	1	Flat Washers

Parts for Installation:

Care must be taken when installing this accessory to ensure damage does not occur to the vehicle. The installation of this accessory should follow approved guidelines to ensure a quality installation. These guidelines can be found in the “Accessory Installation Practices” document.

This document covers such items as:

- Vehicle Protection (use of covers and blankets, cleaning chemicals, etc.).
- Safety (eye protection, re-checking torque procedure, etc.).
- Vehicle Disassembly/ Reassembly (panel removal, part storage, etc.).
- Electrical Component Disassembly/Reassembly (battery disconnection, connector removal, etc.).

Item #	Quantity	Description
1.	1	Console Safe Complete
2.	1	Hardware kit



Service & Warranty Information:

Image Key	Parts information		Warranty Information	
	Part Number	Description	Warranty Time	Labor Op. Code
N/A	00016-35974	Tacoma Console Safe	0.2	ASC011
N/A	00016-35974-01	Center Console Safe - Box	0.4	ASC021
A	00016-35874-02	Center Console Safe - Door	0.3	ASC031
B	00016-35874-03	Center Console Safe - Lock	0.2	ASC041
Not shown	00016-35874-04	Center Console Safe - Hardware kit	NA	NA
C	NA	Master Key- See SET-TSB-17-003	0.1	ASC051
N/A	00016-35874-06	Center Console Safe- Rubber Mat	0.1	ASC061

Labor times include consideration for diagnosis and Administration time

If you are a dealer located outside of the Southeast Region, please contact the SET Accessory Warranty Department at (888) 851-2722 or email accessory.warranty@settoyota.com for claim payment instructions.

Images






Figure 1



Figure 2

Vehicle Disassembly Process:

1. Cover seat with a protective cover and Remove (6) #1 screws from console lid at arrow locations shown in figure 1.

2. Carefully pry lid loose with nylon removal tool from bottom corners to dislodge 4 clips on back of lid. Remove the lid. Clip locations on back side of console lid for reference. Figure 2.



Figure 3

3. Remove the factory console carpet section from the bottom of the console well and discard. Figure. 3.



Figure 4

4. Remove the two (2) 10mm factory mounting bolts from the console well and discard. Figure. 4.




Figure 5

Vehicle Assembly Process:

Note: Make sure the USB Power Ports are not damaged during installation. Figure 5.



Figure 5a.

5. Align the console safe and carefully lower into the factory console well taking care not to scratch console or lid. Figure 5a.



Figure 6

6. Make sure the front edges of the console safe are even side to side with the sides of the factory console +/- 1mm. Figure. 6



Figure 7

7.

The sides of the console safe must not protrude past the edge of the factory console. Figure. 7.



Figure 8

8. Hand start the supplied M6-1.0 x 35mm bolts and flat washers. Torque bolts to 25 in lbs. Figure 8.



Figure 9

9. Reinstall the liner panel into console lid. Figure 9.




Figure 10

10. Install the first rubber floor pad pre-cut with holes over the mounting bolts into the bottom of the console safe. Figure. 10.



Figure 11

11. Install the second rubber floor pad over the first rubber floor pad into the bottom of the console safe.

Figure 11




Figure 12



Figure 13

12. Completed second rubber floor pad installation. See Figure 12.
13. Open door, set dials to 0-0-0 and turn knob to locked position. Roll one or more dials away from 0-0-0 to lock safe door. Insert key and turn counter clockwise to assure key opens lock, close door & turn key back to lock & remove key. Set dials to 0-0-0.
14. Hook key on factory key fob key ring.
15. Affix marketing tag to console as shown in Figure 13.
16. Print Warranty Statement & place in glove box, DIO only.



Illustration

Setting Your Own Combination:

The opening combination code is preset to 0-0-0

1. Combination must be set to opening combination code prior to resetting.
2. Set knob to lock position.
3. On side of lock is code reset button. Press & hold reset button.
4. Set your personal combination by turning dials to desired combination.
5. Release reset button and new opening combination code is set.
6. To lock, rotate one or more dials after dial is turned to lock position.
7. To open lock, turn dials to your personal combination. See Illustration.

Discovering Unknown Combination Using Key:

1. Insert key and turn counter clockwise to unlock and open safe.
2. With key in unlock position; turn each dial until it stops.
3. Once all of dials have stopped, current opening combination code has been discovered & can be reset.

Note: If combination & key are lost, reference SET-TSB-17-003

Vehicle Function Checks:

Checklist - these point MUST be checked to ensure a quality installation.

Check after Installation:



Check Console Lid



Combination Dials



Owner Card & Key



Hardware properly installed



Warranty Statement



Proper Key for Lock

Look For:

Lid function properly

Safe is unlocked & combination set to 0

Card in storage tray, key on key ring.

Hardware tighten & torqued

Installed properly

Place in glove box, DIO only

Operate Lock with Key



LIMITED WARRANTY – SOUTHEAST TOYOTA

SOUTHEAST TOYOTA DISTRIBUTORS, LLC ("we," "our" and "us") provides the following limited warranty on our accessories, excluding tires, ("Accessories" or "Accessory") installed on a Toyota. This limited warranty is not provided by and does not bind or provide benefit to the vehicle dealer, the manufacturer, or Toyota Motor Sales, U.S.A., Inc. This limited warranty does not apply to tires; please consult the tire manufacturer and/or its materials accompanying the vehicle for any warranty terms concerning tires. This limited warranty also does not apply to ToyoGuard Exterior Paint Sealant and ToyoGuard Interior Protector; please consult the ToyoGuard Limited Warranty Certificate for the warranty terms concerning those products.

SCOPE OF LIMITED WARRANTY:

A. Protection:

- i. **Accessories Installed by Southeast Toyota Distributors, LLC on a new Toyota vehicle.** We warrant that, for a period of 36 months or 36,000 miles, whichever occurs first, we will repair or replace (includes labor), free of charge, any defect in such an Accessory due to faulty material or workmanship, or, at our option, provide a full refund of the purchase price of the Accessory. The warranty period begins on the vehicle's In-Service Date, which is the first date the new vehicle is either delivered to an ultimate purchaser, leased, or used as a company car or demonstrator. Accessories installed by Southeast Toyota Distributors, LLC are identified on the vehicle's window sticker (Monroney Label).
- ii. **Accessories Installed by a Toyota Dealer on a Toyota vehicle.** We warrant that, for 12 months, regardless of mileage, from the date such an Accessory was installed on the vehicle or the remainder of the Toyota new vehicle warranty, whichever is longer, we will repair or replace (includes labor), free of charge, any defect in the Accessory due to faulty material or workmanship, or, at our option, provide a full refund of the purchase price of the Accessory. For a new vehicle, the warranty period begins on the vehicle's In-Service Date, which is the first date the new vehicle is either delivered to an ultimate purchaser, leased, or used as a company car or demonstrator.
- iii. **Accessories purchased from a Toyota Dealer but not installed by the Toyota Dealer.** We warrant that, for a period of 12 months, regardless of mileage, from the date the accessory was purchased, we will repair or replace (does not include labor), free of charge, any defect in the Accessory due to faulty material or workmanship, or, at our option, provide a full refund of the purchase price of the Accessory.

B. Limitation of Warranty. This limited warranty does not apply to, and we will not repair, replace, or reimburse you for: (1) wheel balancing and wheel alignments, except for one wheel balancing or alignment during the first 12 months or 12,000 miles, whichever occurs first, from the vehicle's In-Service Date, as defined above, (2) abrasions or dents, whatever their cause, and any failure or damage resulting directly or indirectly from accidents, collisions, impacts from foreign objects, fire, theft, larceny, explosion, malicious mischief, vandalism, civil commotion, riots, war, or any other similar causes, (3) any failure or damage resulting directly or indirectly from lightning, windstorms, hail, water, floods, subfreezing temperatures, airborne chemicals, tree sap, dust, salt, and any other environmental conditions or similar causes, (4) any failure or damage caused by: (a) a failure of any part, other than the Accessory, (b) any misuse, abuse, improper towing, negligence or lack of maintenance of the vehicle or Accessory, (c) the alteration, modification or repair of the Accessory by anyone other than persons expressly authorized by us to perform such alteration, modification or repair, or (d) the use of the vehicle for commercial purposes, competitive driving or racing, (5) any failure or damage, if the Accessory has not been installed according to instructions, (6) any failure or damage occurring outside of Canada, the United States of America, its territories or possessions, (7) except to the extent required by the state whose laws govern this limited warranty, any consequential, secondary, or unreasonable costs that may be suffered as a result of the need to repair or replace the Accessory, including without limitation any loss of use of the vehicle, road service, towing, storage charges, inconvenience, loss of wages and/or income, additional expense incurred, loss of transportation, rental car expense, or any derivative damage to persons or things other than the Accessory, including other parts of the vehicle, or (8) liability for damage to property or for injury to or death of any person, arising out of the operation, maintenance or use of your vehicle whether or not related to the covered Accessory.

C. Exclusive Remedy. If there is a valid claim under this limited warranty for a defect due to faulty material or workmanship in the Accessory, we will, at our option, either: (i) repair, (ii) replace or (iii) provide a full refund of the purchase price of the Accessory. We have no other obligations under this limited warranty. Refunds will be made to the vehicle owner. If the vehicle is leased, the refund will be made to the leasing company.

HOW TO MAKE A CLAIM: In the event of a warranty claim, please contact the nearest Toyota dealer to arrange for repairs. The dealership must receive our prior authorization before making repairs covered by this limited warranty. The dealer will contact Southeast Toyota Distributors, LLC at 1-888-851-2722, select option #5 (Warranty Department), then option #4 (Repairs), for instructions on processing a warranty claim, if they are not already familiar with the process. If you have any questions or concerns regarding repairs covered by this limited warranty, please contact our **Customer Assistance Hotline at 1-800-301-6859**.

OUR DISPUTE RESOLUTION PROGRAM: Your satisfaction is our highest priority. In keeping with that focus, in the event that an issue arises related to this Limited Warranty, we invite you to call our Customer Assistance Hotline at 1-800-301-6859 to discuss it. In most cases, we expect that a satisfactory resolution of your issue can be reached through engagement with that Department. If our Customer Loyalty Department is unable to resolve your issue to your satisfaction, we offer a dispute resolution program administered by the National Center for Dispute Settlement (NCDS) ("the Program"). The purpose of the Program is to resolve disputes in an informal setting before an impartial arbitrator. The Program is free of charge to you (although you must bear the cost of any expert witness or attorney you elect to employ). You are required to complete the Program before exercising rights or seeking remedies under the federal Magnuson-Moss Warranty Act, 15 U.S.C. § 2301 et seq. ("the Act"). If you choose to seek remedies that are not created by the Act, you are not required to use the Program before pursuing such remedies – although the Program is still available to you to resolve the dispute. When utilizing the Program, you will need to provide (a) the vehicle identification number of your vehicle, (b) the identity of your selling and servicing dealerships, (c) the mileage on your vehicle at relevant times, (d) the date and nature of any relevant repairs, (e) legible copies of repair orders and other relevant documents, (f) a summary of the unresolved issue and the requested action, and (g) your contact information. In most cases, the dispute resolution process under the Program will be completed within forty (40) days of your submission of your request and will consist of steps such as an initial eligibility determination, an opportunity for you and us to submit information in writing relating to your claim, an oral hearing, and a decision from the arbitrator. A decision will be binding on you only if you choose to accept it. You may submit a request to NCDS by telephone at their toll free number: (877)-276-8848 or in writing at P.O. Box 463196, Mt. Clemens, MI 48046. You may obtain additional information regarding the Program at www.ncdsusa.org. In the event that the NCDS does not exist or no longer handles disputes for us at the time that you seek to submit a request, you may contact our **Customer Assistance Hotline at 1-800-301-6859** to obtain current information about our dispute resolution programs.

GENERAL LIMITATION OF WARRANTY: THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS WARRANTIES OR LIABILITIES. IN NO EVENT SHALL WE BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES FOR BREACH OF THIS OR ANY OTHER WARRANTY. SOME STATES DO NOT ALLOW THE EXCLUSIONS OR LIMITATIONS OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE INFORMATION OR EXCLUSION MAY NOT APPLY. NO EXPRESS WARRANTY OF FITNESS OR MERCHANTABILITY IS GRANTED BY THIS LIMITED WARRANTY. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THOSE DESCRIBED IN THIS DOCUMENT. ANY IMPLIED WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, WHICH MAY BE APPLICABLE BY OPERATION OF LAW SHALL BE LIMITED TO THE PERIOD OF THIS WRITTEN LIMITED WARRANTY. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATIONS MAY NOT APPLY. THIS LIMITED WARRANTY PROVIDES SPECIFIC LEGAL RIGHTS, AND THERE MAY BE OTHER RIGHTS WHICH VARY FROM STATE TO STATE. ANY ACTION FOR BREACH OF ANY WARRANTY HEREUNDER, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, MUST BE BROUGHT WITHIN A PERIOD NOT EXCEEDING 12 MONTHS AFTER EXPIRATION OF THIS LIMITED WARRANTY. THE REMEDIES SPECIFIED HEREIN AND THOSE SPECIFIED BY APPLICABLE LAW ARE THE ONLY REMEDIES AVAILABLE. WE ASSUME NO OTHER OBLIGATION OR RESPONSIBILITY WITH REGARD TO THE ACCESSORY. WE NEITHER ASSUME, NOR AUTHORIZE ANYONE TO ASSUME FOR US, ANY ADDITIONAL LIABILITY IN CONNECTION HERewith.

GENERAL: This limited warranty describes the complete and exclusive rights that result from the purchase of Accessories. No oral representations or statements may be relied upon. This limited warranty may not be amended or modified, and additional rights may not be granted, unless in a written statement signed by one of our officers. This limited warranty shall be governed by the laws of the state where the vehicle is purchased, excluding laws concerning conflicts of law. We may delegate the performance of our duties and obligations and assign our rights and benefits hereunder. For inquiries regarding this limited warranty, we can be contacted directly at **Customer Assistance Hotline at 1-800-301-6859**, or by mail to: **Southeast Toyota Distributors, LLC, Attention: Customer Loyalty Department, 100 Jim Moran Boulevard, Deerfield Beach, Florida 33442.**