



INSTALLATION INSTRUCTIONS

**For 68499 Light Bar
For Hummer 2**

As you read these instructions, you may see **NOTES**, **CAUTIONS** and **WARNINGS**. Each message has a specific purpose. **NOTES** are additional information to help you complete a procedure. **CAUTIONS** are safety messages that indicate a potentially hazardous situation, which, if not avoided, may result in minor or moderate injury. A **CAUTION** may also be used to alert against unsafe practice. **WARNINGS** are safety messages that indicate a potentially hazardous situation, which, if not avoided could result in serious injury. **CAUTIONS** and **WARNINGS** identify the hazard, indicate how to avoid the hazard, and advise of the probable consequence of not avoiding the hazard. **PLEASE WORK SAFELY!**

PARTS LIST FOR 64535 or 64737

PART NO.	QUANTITY	DESCRIPTION
68497	1	Light Bar
68498	1	Hardware Kit

TORQUE SPECIFICATIONS

<u>BOLT SIZE</u>	<u>TORQUE</u>
¼ inch	10-12 ft. lbs.

1. Install the light bar to the factory grille guard. The light bar mounts to the factory grille guard using factory holes. Hold the light bar in place and mount using the 1/4" hardware provided. Install the four bolts with flat washers through the holes in the factory grille guard and then through the light bar. Install a flat washer and lock nut onto each bolt. See Figure 1.



2. Once all four bolts are installed, align the light bar to the factory grille guard and torque the four bolts to 10-12 ft/lbs. See Figure 2.

